

COMATRA TELEHANDLER TPMS

Featuring the unique inside the rim fitted pressure sensors!

Don't get caught out by a roll-over !

A 5% reduction in tire pressure from the manufacturer's values can result in a 30% reduction in capacity at certain points on the load-height-radius curve which could result in the vehicle overturning !

The most critical situation is the one of having an under inflated tire with a load in the air drastically altering the rough terrains' or telescopic handlers' stability ending up in a **fatal accident** !



Improve the Safe Use of Rough Terrain Forklifts and Telescopic Handlers !



4-6 Wheels

bar / kPa or psi
Temp in °C or °F

REALTIME TIRE MONITORING:

Pressure range : 0.4 bar ~ 7.0 bar / 5.8 psi ~ 101 psi.

Audiovisual warnings :

- in case of low or high pressure, leaks, pressure drops.
- in case of tire overheating : + 80°C / 176°F.
- Improves steering and braking control.
- Enhanced cornering stability.
- An efficient step forward to drastically prevent roll-overs.



Unique internal valve mounted sensors
Fit perfectly in the ETRTO V5.01.1 - TR618A rim hole.



Source : www.profi.com



Source : www.ppconstructionsafety.com

COMATRA - BELGIUM

Hogeweg 33
3800 Ordingen
BELGIUM

TEL + 32 11 68 22 39.

FAX + 32 11 68 60 26.

E-mail : info@comatra.be

Website : www.tp2agric.com